



PolyGard®

Warning Horn WH230/24

Warning horn in stable plastic housing (ABS) according to VDI 2053.

APPLICATION

All-purpose audio warning hooter with 32 adjustable sounds, incl. DIN tone for fire-detection and safety systems in accordance with the VdS directives.

FEATURES

- Simple maintenance
- Continuous operation
- Long life-time
- Reliable



Warning horn WH230/24

TYPES

Warning horn 230 V AC, 98 dB:	WH-230-98
Warning horn 230 V AC, 108 dB:	WH-230-108
Warning horn 24 V DC, 98 dB:	WH-24-98
Warning horn 24 V DC, 108 dB:	WH-24-108

SPECIFICATIONS

Electrical

Power supply	110 - 240 V AC, 50 Hz or 9 - 28 V DC
Power consumption	Max. 35 mA
Audio frequency	32 arbitrary sounds, incl. DIN tone
Acoustic pressure	64 dB (A) - 111 dB (A)

Operating Environment

Humidity	0 – 95 % RH non condensing
Working temperature	-10 °C to +55 °C
Storage temperature	-10 °C to +55 °C
Pressure range	Atmospheric ± 10 %

Physical characteristics

Enclosure material	Thermoplastic (ABS), shock-resistant
Enclosure colour	Red
Dimensions (d x H)	Ca. 93 * 93 mm
Weight	0.32 kg
Protection class	IP 54
Mounting	Wall and ceiling installation
Cable entry	Ca. 12 mm diameter
Wire connection	Screw-type terminals, min. 0.28 mm ² , max. 2.5 mm ²

Directives	VdS
-------------------	-----

